

Main

Device short name	RIM
Product or component type	Restraint interface module
Accessory / separate part category	Protection accessory

Complementary

Input power	10 W
Input voltage	120 V AC
AWG gauge	AWG 24AWG 18
Mounting support	Rail NT13, class 8501 Rail N10
Tightening torque	6.215.05 lbf.in (0.71.7 N.m) 0.00030.001 in² (0.200.82 mm²) AWG 24AWG 18)

Environment

Product certifications	UL
	CSA

Packing Units

Nov 8, 2024

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.700 in (9.398 cm)
Package 1 Width	5.0000000000 in (12.700 cm)
Package 1 Length	9.600 in (24.384 cm)
Package 1 Weight	24.000 oz (680.388 g)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

The second personal second sec		
Mercury Free		
Rohs Exemption Information	Yes	
Reach Regulation	REACh Declaration	
Eu Rohs Directive	Compliant with Exemptions	
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	